according to WHS Regulations

Print date: 15.05.2023 Revision date: 15.05.2023

1 Identification

Product Name: XLam CLT Panel Untreated

Other Means of Identification: Article

Recommended Use of the Chemical and Restriction on Use: Timber panels for construction applications.

Details of Manufacturer or Importer:

XLam Australia Pty Ltd

160 Kent St

Maryborough QLD 4650

Phone Number: 02 6042 8700

Emergency telephone number: 02 6042 8700

2 Hazard(s) Identification

Hazardous Nature:

Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

This product is considered as article and is as such exempted from the UN-GHS classification requirements. The classification based on the hazardous substances contained in the product is provided below for information purposes only.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition), IATA and IMDG/IMSBC.

The product is not classified, according to the Globally Harmonised System (GHS).

Signal Word None

Hazard Statements None

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components: None

Non Hazardous Components:		
CAS: 2758886-87-0	Methylendiisocyanate-based polyurethane polyurea polyether polymer	<1%
CAS: 67762-90-7	Siloxanes and silicones, dimethyl, reaction products with silica	<0.03%
CAS: 6425-39-4	2,2'-dimorpholinyldiethyl ether	<0.01%
CAS: 31885-97-9	Polyethylene glycol dibutyl ether	<0.01%
	Softwood(s)	99%

Additional information:

Other components include:

X-Seal end grain (less than 0.02%).

4 First Aid Measures

Inhalation:

Inhalation is not considered a potential route of exposure as sold, however may occur during further processing (snading, drilling, cutting etc.).

If dust is inhaled, remove to fresh air. Seek medical attention if breathing problems develop.

Skin Contact:

In case of dust skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if irritation occurs.

(Contd. on page 2)

according to WHS Regulations

Print date: 15.05.2023 Revision date: 15.05.2023

Product Name: XLam CLT Panel Untreated

(Contd. of page 1)

Eye Contact:

In case of dust eye contact, rinse with water for several minutes, including under eyelids. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give 1-2 glasses of water to drink in small sips. Never give anything by mouth to an unconscious person. Seek medical attention.

Symptoms Caused by Exposure:

Inhalation: Dust may cause respiratory irritation.

Skin Contact: Dust may cause skin irritation and an allergic skin reaction.

Eye Contact: Dust may cause mechanical eye irritation, redness and lachrymation. Ingestion: May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.

5 Fire Fighting Measures

Suitable Extinguishing Media: Water fog or fine spray.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon, oxides of nitrogen and other hydrocarbons.

Product is not flammable but may burn or decompose in a fire.

Containers close to fire should be removed only if safe to do so. Use water spray to cool fire exposed containers.

Minimise run-off from fire fighting entering drains or water courses.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved dust/particulate filter respirator and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Pick up large pieces and clean up the small pieces and dusts with a vacuum or by a wet sweeping technique. Do not use compressed air.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Protect from heat, sparks, open flames and other sources of ignition.

8 Exposure Controls and Personal Protection

Exposure Standards:

Softwood

WES STEL: 10* mg/m³ TWA: 5* mg/m³

Sen., *as dust

according to WHS Regulations

Print date: 15.05.2023 Revision date: 15.05.2023

Product Name: XLam CLT Panel Untreated

(Contd. of page 2)

Engineering Controls:

Ensure adequate ventilation of the working area, keeping airborne concentrations below occupational exposure standards.

Respiratory Protection:

Where an inhalation risk exists, wear approved particulate respirator (filter type P1). At high dust levels, wear a powered air purifying respirator (PAPR) with P3 filter or an air-line respirator or a full-face P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Leather or cotton gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eve and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form: Solid

Colour:Translucent greenOdour:Nearly odourless

Odour Threshold:

pH-Value:

Melting point/freezing point:
Initial Boiling Point/Boiling Range:
Flash Point:

No information available
No information available
No information available
No information available

Flammability (solid, gas): Not flammable

Auto-ignition Temperature: No information available Decomposition Temperature: No information available

Explosion Limits:

Lower:
Upper:
Vapour Pressure:
Relative Density:
Vapour Density:
No information available

Solubility in Water: Insoluble

Partition Coefficient (n-octanol/water): No information available **Viscosity:** No information available

10 Stability and Reactivity

Possibility of Hazardous Reactions: No dangerous reactions known under conditions of normal use.

Chemical Stability: Stable at ambient temperature and under normal conditions of storage and use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: Oxides of carbon, oxides of nitrogen and other hydrocarbons.

(Contd. on page 4)

according to WHS Regulations

Print date: 15.05.2023 Revision date: 15.05.2023

Product Name: XLam CLT Panel Untreated

(Contd. of page 3)

11 Toxicological Information

Toxicity:

Acute Health Effects

Inhalation: Dust may cause respiratory irritation.

Skin: Dust may cause skin irritation and an allergic skin reaction. **Eye:** May cause mechanical eye irritation, redness and lachrymation.

Ingestion: May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met. **Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity:

Based on classification principles, the classification criteria are not met. Wood dust is classified by IARC as Group 1 - Carcinogenic to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects: No data associated with long term health effects.

Existing Conditions Aggravated by Exposure: No data available.

12 Ecological Information

Ecotoxicity:

Aquatic toxicity:

No adverse ecological effects are expected. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and Degradability: No data available on finished product.

Bioaccumulative Potential: No data available on finished product.

Mobility in Soil: No data available on finished product.

Other adverse effects: No further relevant information available.

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulated
Proper Shipping Name Not regulated
Dangerous Goods Class Not regulated

according to WHS Regulations

Print date: 15.05.2023 Revision date: 15.05.2023

Product Name: XLam CLT Panel Untreated

(Contd. of page 4)

Packing Group: Not regulated

15 Regulatory Information

Australian Inventory of Industrial Chemicals:

All components are on the inventory, or in compliance with the inventory.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Poison Schedule:

Not a scheduled poison.

16 Other Information

Date of Preparation or Last Revision: 24.04.2023

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society)

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Disclaimer

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. XLam Australia Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used. This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - July 2020".